✓ avantor<sup>™</sup>



Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 13/05/2019 Date of issue: 08/01/2014

Version: 3.0

# SECTION 1: Identification of the Substance/mixture and of the Company/Undertaking

## 1.1. Product Identifier

Product form Product Name Synonyms Mixture MED-6655 Fluorosilicone Dispersion

## 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

#### **1.2.1. Relevant Identified Uses** Use of the Substance/Mixture

re For professional use only.

#### 1.2.2. Uses Advised Against

No additional information available

## 1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology Europe 1198 Avenue Maurice Donat Le Natura Bt. 2 06250 Mougins France +33 4 92 96 93 31 ehs@nusil.com www.nusil.com

## 1.4. Emergency Telephone Number

Emergency Number

: +(44)-870-8200418 +(353)-19014670

## **SECTION 2: Hazards Identification**

## 2.1. Classification of the Substance or Mixture

#### Classification According to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225 Skin Irrit. 2 H315 Eye Dam. 1 H318 STOT SE 3 H335

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

Labelling According to Regulation (EC) No. 1272/2008 [CLP]

Hazard Pictograms (CLP)



GHS02 GHS05 GHS07
Danger
H225 - Highly flammable liquid and vapour.
H315 - Causes skin irritation.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.

Safety Data Sheet

Precautionary Statements (CLP)	P210 - Keep away from heat, hot surfaces, sparks, open flames
	and other ignition sources. No smoking.
	P233 - Keep container tightly closed.
	P240 - Ground and bond container and receiving equipment.
	P241 - Use explosion-proof electrical, ventilating, and lighting
	equipment.
	P242 - Use non-sparking tools.
	P243 - Take action to prevent static discharges.
	P261 - Avoid breathing vapors, mist, or spray
	P264 - Wash hands, forearms, and exposed areas thoroughly after handling
	P271 - Use only outdoors or in a well-ventilated area.
	P280 - Wear eye protection, face protection, protective
	clothing, protective gloves
	P302+P352 - IF ON SKIN: Wash with plenty of water
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately al
	contaminated clothing. Rinse skin with water.
	P304+P340 - IF INHALED: Remove person to fresh air and keep
	comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for
	several minutes. Remove contact lenses, if present and easy t do. Continue rinsing.
	P310 - Immediately call a POISON CENTER or doctor
	P312 - Call a POISON CENTRE or doctor if you feel unwell.
	P321 - Specific treatment (see Section 4 on this SDS)
	P332+P313 - If skin irritation occurs: Get medical
	advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P370+P378 - In case of fire: Use appropriate media (see sectio 5) to extinguish
	P403+P233+P235 - Store in a well-ventilated place. Keep
	container tightly closed. Keep cool.
	P405 - Store locked up.
	P501 - Dispose of contents/container to hazardous or special
	waste collection point, in accordance with local, regional, national and/or international regulation.
.3. Other Hazards	Ğ
Other Hazards Not Contributing	Exposure may aggravate pre-existing eye, skin, or respiratory

## **SECTION 3: Composition/Information on Ingredients**

#### 3.1. Substances

to the Classification

Not applicable

#### 3.2. Mixture

conditions.

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product Identifier	%	Classification According to Regulation (EC) No. 1272/2008 [CLP]
Siloxanes and Silicones, methyl 3,3,3-trifluoropropyl, hydroxy- terminated	(CAS-No.) 68607-77-2	40 - 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
tert-Butyl acetate substance with national workplace exposure limit(s) (AT, BE, CH, CZ, DE, DK, ES, FI, FR, GB, GR, IE, LV, PL, PT, SE, SK)	(CAS-No.) 540-88-5 (EC-No.) 208-760-7 (EC Index-No.) 607-026-00-7	30 - 50	Flam. Liq. 2, H225
Silanetriol, ethyl-, triacetate	(CAS-No.) 17689-77-9 (EC-No.) 241-677-4	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
Silanetriol, methyl-, triacetate	(CAS-No.) 4253-34-3 (EC-No.) 224-221-9	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Full text of H-statements: see section 16

## **SECTION 4: First Aid Measures**

#### 4.1. **Description of First-aid Measures**

First-Aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).		
First-Aid Measures After Inhalation	Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.		
First-Aid Measures After Skin Contact	Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.		
First-Aid Measures After Eye Contact	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.		
First-Aid Measures After Ingestion	Seek medical attention if a large amount is swallowed. Rinse mouth. Do NOT induce vomiting.		
4.2. Most Important Symptoms and Effects Both Acute and Delayed			
Symptoms/Effects	Causes skin irritation. Causes serious eye damage. May cause drowsiness and dizziness. May cause respiratory irritation.		
Symptoms/Effects After Inhalation	May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.		
Symptoms/Effects After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis.		
Symptoms/Effects After Eye Contact	Causes permanent damage to the cornea, iris, or conjunctiva.		

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/Effects After Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms Repeated exposure may cause skin dryness or cracking.

**4.3.** Indication of Any Immediate Medical Attention and Special Treatment Needed If you feel unwell, seek medical advice (show the label where possible).

## **SECTION 5: Firefighting Measures**

#### 5.1. Extinguishing Media

Suitable Extinguishing Media	Water spray, fog, carbon dioxide, foam, dry chemical.	
Unsuitable Extinguishing Media	Do not use a heavy water stream. Use of heavy stream of water	
	may spread fire. Application of water stream to hot product	
	may cause frothing and increase fire intensity.	
5.2. Special Hazards Arising From the Substance or Mixture		
Fire Hazard	Highly flammable liquid and vapour.	
Explosion Hazard	May form flammable/explosive vapour-air mixture.	

בגטוטאטרו הטבטוט	
Reactivity	Reacts violently with (strong) oxidizers: (increased) risk of
	fire/explosion.
Hazardous Decomposition	Carbon oxides (CO, CO <sub>2</sub> ). Silicon oxides. Will decompose
Products in Case of Fire	above 150 °C (> 300 °F) releasing formaldehyde vapours.
	Formaldehyde is a potential carcinogen and can act as a skin
	and respiratory sensitizer. Formaldehyde can also cause
	respiratory and eye irritation. Isobutylene. Acetic acid. Oxides
	of tin.
5.3. Advice for Firefighters	
Precautionary Measures Fire	Exercise caution when fighting any chemical fire.
Firefighting Instructions	Do not breathe fumes from fires or vapours from

Firefighting InstructionsDo not breathe fumes from fires or vapours from<br/>decomposition.Protection During FirefightingDo not enter fire area without proper protective equipment,<br/>including respiratory protection.

## **SECTION 6: Accidental Release Measures**

## 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures	Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Avoid contact with skin, eyes and clothing. Avoid breathing (vapor, mist, spray).
6.1.1. For Non-Emergency Pers	
Protective Equipment	Use appropriate personal protective equipment (PPE).
Emergency Procedures	Evacuate unnecessary personnel.
6.1.2. For Emergency Respond	lers
Protective Equipment	Equip cleanup crew with proper protection.
Emergency Procedures	Stop leak if safe to do so. Eliminate ignition sources. Ventilate
	area.
6.2. Environmental Precau	tions
Prevent entry to sewers and pu	ublic waters. Notify authorities if liquid enters sewers or public waters.
6.3. Methods and Material	s for Containment and Cleaning Up

For Containment Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Methods For Cleaning Up	Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Contact competent authorities
	after a spill.

#### 6.4. Reference to Other Sections

See Section 8 for advice on personal protective equipment and Section 13 for disposal considerations.

## **SECTION 7: Handling And Storage**

#### 7.1. Precautions for Safe Handling

Additional Hazards When Processed	Handle empty containers with care because residual vapours are flammable.
Precautions for Safe Handling	Avoid contact with skin and eyes. Take precautionary measures against static discharge. Use only non-sparking tools. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.
7.2. Conditions for Safe Storag	ge, Including Any Incompatibilities
Technical Measures	Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Comply with applicable regulations.
Storage Conditions	Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place.
Incompatible Materials	Strong acids. Strong bases. Strong oxidizers.
7.3. Specific End Use(S)	-

For professional use only.

## SECTION 8: Exposure Controls/Personal Protection

#### tert-Butyl acetate (540-88-5) Austria MAK (mg/m<sup>3</sup>) 96 mg/m<sup>3</sup> Austria MAK (ppm) 20 ppm Austria MAK Short time value 96 mg/m<sup>3</sup> $(mg/m^3)$ Austria MAK Short time value (ppm) 20 ppm Austria 96 mg/m<sup>3</sup> OEL - Ceilings (mg/m<sup>3</sup>) Austria OEL - Ceilings (ppm) 20 ppm Limit value (mg/m<sup>3</sup>) 238 mg/m<sup>3</sup> Belgium Limit value (ppm) 50 ppm Belgium

#### 8.1. Control Parameters

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Belgium	REACH) with its amendment Regulation (EU) 2015/830 Short time value (mg/m³)	712 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	150 ppm
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	966 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	200 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	1210 mg/m³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	250 ppm
Czech Republic	Expoziční limity (PEL) (mg/m³)	950 mg/m³
Denmark	Grænseværdie (langvarig) (mg/m³)	710 mg/m³ (Butyl acetate, all isomers)
Denmark	Grænseværdie (langvarig) (ppm)	150 ppm (Butyl acetate, all isomers)
Finland	HTP-arvo (8h) (mg/m³)	720 mg/m³ (Butyl acetate)
Finland	HTP-arvo (8h) (ppm)	150 ppm (Butyl acetate)
Finland	HTP-arvo (15 min)	960 mg/m³ (Butyl acetate)
Finland	HTP-arvo (15 min) (ppm)	200 ppm (Butyl acetate)
France	VME (mg/m³)	950 mg/m³
France	VME (ppm)	200 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	96 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece	OEL TWA (mg/m³)	950 mg/m³
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m³)	1190 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	250 ppm
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	950 mg/m³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	600 ppm (calculated)
Latvia	OEL TWA (mg/m³)	200 mg/m <sup>3</sup>
Poland	NDS (mg/m³)	900 mg/m <sup>3</sup>
Poland	NDSCh (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Portugal	OEL TWA (ppm)	200 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Slovakia	NPHV (Hraničná) (mg/m³)	384 mg/m <sup>3</sup>
Slovenia	OEL TWA (mg/m <sup>3</sup> )	96 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	20 ppm
Slovenia	OEL STEL (mg/m³)	96 mg/m <sup>3</sup>

EN (English)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Slovenia	OEL STEL (ppm)	20 ppm
Spain	VLA-ED (mg/m³)	966 mg/m³
Spain	VLA-ED (ppm)	200 ppm
Sweden	nivågränsvärde (NVG) (mg/m³)	500 mg/m³ (Butyl acetates)
Sweden	nivågränsvärde (NVG) (ppm)	100 ppm (Butyl acetates)
Sweden	kortidsvärde (KTV) (mg/m³)	700 mg/m³ (Butyl acetates)
Sweden	kortidsvärde (KTV) (ppm)	150 ppm (Butyl acetates)
Switzerland	KZGW (mg/m³)	480 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	100 ppm
Switzerland	MAK (mg/m³)	240 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	50 ppm
United Kingdom	WEL TWA (mg/m³)	966 mg/m³
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m³)	1210 mg/m³
United Kingdom	WEL STEL (ppm)	250 ppm

#### 8.2

<b>3.2.</b> Exposure Controls	
Appropriate Engineering Controls	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases/vapours may be released. Take precautionary measures against static discharges. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure all national/local regulations are observed.
Personal Protective Equipment	Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.
Materials for Protective Clothing	Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.
Hand Protection	Wear chemically resistant protective gloves.
Eye Protection Skin and Body Protection	Chemical safety goggles. Wear suitable protective clothing.
Respiratory Protection	Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
Environmental Exposure Controls	Do not allow the product to be released into the environment.
Consumer Exposure Controls	Do not eat, drink or smoke during use.

## **SECTION 9: Physical and Chemical Hazards**

#### Information on Basic Physical and Chemical Properties 9.1.

EN (English)

**Physical State** Appearance Odour

Liquid White. No data available

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

enament Regulation (EU) 2015/830
No data available
98 °C (208 °F)
4,4 °C (40 °F)
No data available
< 1 (water = 1)
No data available
ater No data available
No data available
No data available
No data available
No data available
No data available
30 - 50 %

## **SECTION 10: Stability and Reactivity**

#### 10.1. Reactivity

Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion.

#### 10.2. Chemical Stability

Highly flammable liquid and vapour.

#### 10.3. Possibility Of Hazardous Reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions To Avoid

Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

#### 10.5. Incompatible Materials

Strong acids. Strong bases. Strong oxidizers.

#### 10.6. Hazardous Decomposition Products

None expected under normal conditions of use.

## **SECTION 11: Toxicological Information**

#### 11.1. Information On Toxicological Effects

Acute Toxicity	Not classified		
tert-Butyl acetate (540-88-5)			
LD50 Oral Rat	4500 mg/kg		
LD50 Oral	3300 mg/kg		
LD50 Dermal Rabbit	> 2000		
LC50 Inhalation Rat	> 9482 mg/m³ (Exposure time: 4 h)		
LC50 Inhalation Rat 5157 ppm/4h			

### Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its ame	ndment Regulation (EU) 2015/830		
tert-Butyl acetate (540-88-5)			
LC50 Inhalation Rat	13,3 mg/l/4h		
Silanetriol, ethyl-, triacetate (17689	9-77-9)		
LD50 Oral Rat	1460 mg/kg		
LD50 Oral	1462 mg/kg		
Silanetriol, methyl-, triacetate (425	53-34-3)		
LD50 Oral Rat	1437 - 1780 mg/kg		
LD50 Oral	1602 mg/kg		
Skin Corrosion/Irritation Eye Damage/Irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity Reproductive Toxicity Specific Target Organ Toxicity (Single Exposure)	Causes skin irritation. Causes serious eye damage. Not classified Not classified Not classified May cause respiratory irritation.		
Specific Target Organ Toxicity (Re Exposure)	peated Not classified		
Aspiration Hazard	Not classified		

## **SECTION 12: Ecological Information**

#### 12.1. Toxicity

Ecology - General	Not classified	
tert-Butyl acetate (540-88-5)		
LC50 Fish 1	296 - 362 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	

#### 12.2. Persistence and Degradability

MED-6655	
Persistence and Degradability	Not established.
Dibutyltin diacetate (1067-33-0)	
Persistence and Degradability	Not established.
12.3. Bioaccumulative Potentic	الا
MED-6655	
Bioaccumulative potential	Not established.
tert-Butyl acetate (540-88-5)	
Log Pow	1,38
Silanetriol, methyl-, triacetate (42	53-34-3)

# Log Pow

0,25 KowWin

EN (English)

## 12.4. Mobility in Soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other Adverse Effects

Other Information

Avoid release to the environment.

## SECTION 13: Disposal Considerations

#### 13.1. Waste Treatment Methods

Product/Packaging Disposal	Dispose of waste material in accordance with all local,
Recommendations	regional, national, and international regulations.
Additional Information	Handle empty containers with care because residual vapours
	are flammable.
Ecology - Waste Materials	Avoid release to the environment.

## **SECTION 14: Transport Information**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In accordance with ADR / RID / IMDG / IATA / ADN

IMDG	IATA	ADN	RID	
r	I	1		
1123	1123	1123	1123	
14.2. UN Proper Shipping Name				
BUTYL ACETATES	BUTYL ACETATES	BUTYL ACETATES	BUTYL ACETATES	
14.3. Transport Hazard Class(Es)				
3	3	3	3	
14.4. Packing Group				
ntal Hazards				
Dangerous for	Dangerous for	Dangerous for	Dangerous for	
the environment	the environment	the environment	the environment	
:No	: No	:No	:No	
Marine pollutant : No				
	r 1123 Shipping Name BUTYL ACETATES azard Class(Es) 3 Coup Il ntal Hazards Dangerous for the environment : No	r 1123 Shipping Name BUTYL ACETATES BUTYL ACETATES azard Class(Es) 3 3 3 3 3 3 3 3 3 3 3 3 3	r       1123       1123         1123       1123       1123         Shipping Name       BUTYL ACETATES       BUTYL ACETATES         BUTYL ACETATES       BUTYL ACETATES       BUTYL ACETATES         azard Class(Es)       3       3         3       3       3         intal Hazards       Dangerous for the environment : No       Dangerous for the environment : No         No       Marine pollutant       INO	

#### 14.6. Special Precautions For User

No additional information available

**14.7. Transport in Bulk According to Annex II of MARPOL and The IBC Code** Not applicable

## SECTION 15: Regulatory Information

# 15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

#### 15.1.2. National Regulations

No additional information available

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other Information**

#### Indication of Changes -

Section	Section Hea	der	Change	Date Changed	
1	Identification of the		Modified	13/05/2019	
	substance/mixture and of				
	the company/undertaking				
3		/information	Modified	13/05/2019	
	on ingredien	its			
	reparation or L	_atest 13/05	5/2019		
Revision					
Data Sou	rces		nation and data obtained an	5	
			afety data sheet could come	•	
			al government regulatory body websites, uct/ingredient manufacturer or supplier specific		
		-	-		
information, and/or resources that include substance spec data and classifications according to GHS or their subsequ				•	
adoption of GHS.					
Other Info	ormation		ording to Regulation (EC) No.	1907/2006 (REACH) with its	
		ame	ndment Regulation (EU) 2015/	830	
Full Text o	f H- and EUH-s	tatements:			
Acute	e Tox. 4 (Oral)	Acute toxicity	(oral), Category 4		
Eye D	0am. 1	Serious eye damage/eye irritation, Category 1			
Eye Ir	rit. 2	Serious eye damage/eye irritation, Category 2			
Flam.	Liq. 2	Flammable liquids, Category 2			
Skin C	Corr. 1B	Skin corrosion/irritation, Category 1B			
Skin C	Corr. 1C	Skin corrosion/irritation, Category 1C			
Skin Ir	rit. 2	Skin corrosion/irritation, Category 2			
STOT	RE 1	Specific target organ toxicity — Repeated exposure, Category 1			
STOT	SE 1	Specific target organ toxicity — Single exposure, Category 1			
STOT	SE 3	Specific target organ toxicity — Single exposure, Category 3,			
		Respiratory tract irritation			
H225		Highly flammable liquid and vapour.			
H302		Harmful if swallowed.			
H314		Causes severe skin burns and eye damage.			
H315		Causes skin irritation.			
H318		Causes serious eye damage.			
H319		Causes serious eye irritation.			
H335		May cause respiratory irritation.			
H370		Causes damage to organs.			
H372		Causes damage to organs through prolonged or repeated exposure.			

~

#### Abbreviations and Acronyms

ACGIH – American Conference of Governmental Industrial Hygienists ADN – European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road ATE - Acute Toxicity Estimate

NDS - Najwyzsze Dopuszczalne Stezenie NDSCh - Najwyzsze Dopuszczalne Stezenie Chwilowe NDSP - Najwyzsze Dopuszczalne Stezenie Pulapowe NOAEL - No-Observed Adverse Effect Level NOEC - No-Observed Effect Concentration NRD - Nevirsytinas Ribinis Dydis

EN (English)

#### Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

BCF - Bioconcentration Factor NTP – National Toxicology Program BEI - Biological Exposure Indices (BEI) OEL - Occupational Exposure Limits PBT - Persistent, Bioaccumulative and Toxic BOD – Biochemical Oxygen Demand CAS No. - Chemical Abstracts Service Number PEL - Permissible Exposure Limit CLP - Classification, Labeling and Packaging Regulation (EC) No 1272/2008 pH – Potential Hydrogen COD - Chemical Oxygen Demand REACH – Registration, Evaluation, Authorisation, and Restriction of Chemicals EC – European Community RID - Regulations Concerning the International Carriage of Dangerous Goods by Rail EC50 - Median Effective Concentration SADT - Self Accelerating Decomposition Temperature - European Economic Community SDS - Safety Data Shee EINECS – European Inventory of Existing Commercial Chemical Substances EmS-No. (Fire) - IMDG Emergency Schedule Fire STEL - Short Term Exposure Limit STOT - Specific Target Organ Toxicity TA-Luft - Technische Anleitung zur Reinhaltung der Luft EmS-No. (Spillage) - IMDG Emergency Schedule Spillage TEL TRK – Technical Guidance Concentrations ThOD – Theoretical Oxygen Demand EU - European Union ErC50 - EC50 in Terms of Reduction Growth Rate GHS - Globally Harmonized System of Classification and Labeling of Chemicals TLM - Median Tolerance Limit IARC - International Agency for Research on Cancer TLV - Threshold Limit Value IATA - International Air Transport Association TPRD - Trumpalaikio Poveikio Ribinis Dydis IBC Code - International Bulk Chemical Code IMDG - International Maritime Dangerous Goods TRGS 510 - Technische Regel für Gefahrstoffe 510 - Lagerung von Gefahrstoffen in ortsbeweglichen Behältern IPRV - Ilgalaikio Poveikio Ribinis Dydis TRGS 552 – Technische Regeln für Gefahrstoffe - N-Nitrosamine IOELV - Indicative Occupational Exposure Limit Value TRGS 900 - Technische Regel für Gefahrstoffe 900 – Arbeitsplatzgrenzwerte LC50 - Median Lethal Concentration TRGS 903 - Technische Regel für Gefahrstoffe 903 - Biologische Grenzwerte LD50 - Median Lethal Dose TSCA - Toxic Substances Control Act I OAFL - Lowest Observed Adverse Effect Level TWA - Time Weighted Average VOC – Volatile Organic Compounds LOEC - Lowest-Observed-Effect Concentration Log Koc - Soil Organic Carbon-water Partitioning Coefficient Log Kow - Octanol/water Partition Coefficient VLA-EC - Valor Límite Ambiental Exposición de Corta Duración VLA-ED - Valor Límite Ambiental Exposición Diaria Log Pow - Ratio of the equilibrium concentration (C) of a dissolved substance in a VLE - Valeur Limite D'exposition two-phase system consisting of two largely immiscible solvents, in this case octanol VME - Valeur Limite De Moyenne Exposition vPvB - Very Persistent and Very Bioaccumulative and water MAK - Maximum Workplace Concentration/Maximum Permissible Concentration WEL - Workplace Exposure Limit MARPOL - International Convention for the Prevention of Pollution WGK - Wassergefährdungsklasse Nusil EU GHS SDS

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.



# Silicone Sales & Services UK - Ireland - Benelux

© 2019 - Polymer Systems Technology Limited™ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF

# tel: +44 (0) 1494 446610

## web: https://www.silicone-polymers.com

# email: sales@silicone-polymers.co.uk

